

FLAT

EW-WAX

Wax Standard



EW-WAX is an economical standard wax that provides unfailing performances on a wide range of substrates.

Designed to print barcodes on labels and tags up to 8 IPS, this ribbon offers a high optical density quality, well-defined images and prints with very low temperatures.

It is a very versatile ribbon that provides reliable prints on vellum and coated paper.

TECHNICAL FEATURES

COLOR	Black
BACK COATING	Silicone base
IMAGE DARKNESS	1.82 ODR
INK MELTING POINT	60°±3°C
STORAGE CONDITIONS	12 Months / 5-35°C 20-80% Relative Humidity Rate
PRINTING SPEED	8 IPS
FILM THICKNESS	4.5 microns
TOTAL THICKNESS	7.1 microns



STANDARD

MISS BEE
EW-WAX



PREMIUM

WRITE G
WRITE W+
WRITE H



EXCELLENT

WE 22
WRITE K

PRINTING FEATURES

DARKNESS



SCRATCH RESISTANCE



SHARPNESS



PRINT TEMPERATURE



PRINT SPEED



BARCODE 90°



EW-WAX

Wax Standard

RECOMMENDED APPLICATIONS



LOGISTICS




PACKAGING



CHEMICAL



FOOD & BEVERAGE



HORTICULTURE



AUTOMOTIVE



MEDICAL



ELECTRONICAL



HEALTH AND BEAUTY



TEXTILE

RECOMMENDED SUBSTRATES



Vellum Paper

Matt coated Paper

Semi-gloss Paper

CHEMICALS RESISTANCE



ALCOHOL



GASOLINE



GASOLINE + OIL



COMPLIANCES



ISEGA



T H E R M A L
T R A N S F E R
R I B B O N

E.U.R.O. Srl
Via Pacinotti, 28
30033 Noale (VE)

Tel. +39 041 3195211
ttr@eurosrl.com
www.eurosrl.com

All information in the datasheet has been produced for the exclusive use of E.u.r.o. s.r.l. Any reproduction, even partial, is prohibited. The BEE trademark is registered. The measured values may slightly vary in a different environment. The information contained may change without notice or notification. The information presented here is a general guideline, for further information please contact our offices. All product certifications have been registered with the original codes of the raw material.