

FLAT

WRITE WR

Soft Wax/resin



WRITE WR is a soft wax/resin, the step of detachment from the wax range to the wax/resin range. It provides a reliable scratch resistance on matt and paper substrates, sharp printing with low temperature settings.

Unbeatable on printing barcodes for pharmaceutical products, storage and warehousing, this formulation is more durable than a wax premium and provides a higher resistance to strong manipulations, temperature swings and humidity.

TECHNICAL FEATURES

| | |
|--------------------|-----------------------------------------------------|
| COLOR | Black |
| BACK COATING | Silicone base |
| IMAGE DARKNESS | 2.13 ODR |
| INK MELTING POINT | 73°±3°C |
| STORAGE CONDITIONS | 12 Months / 5-35°C 20-80% Relative Humidity Rate |
| PRINTING SPEED | 8 IPS |
| FILM THICKNESS | 4.5 microns |
| TOTAL THICKNESS | 8.6 microns |



STANDARD

WRITE WR

WRITE M



PREMIUM

QUEEN BEE

WRITE WR+



EXCELLENT

WR E28

PRINTING FEATURES

DARKNESS



SCRATCH RESISTANCE



SHARPNESS




PRINT TEMPERATURE



PRINT SPEED



BARCODE 90°



WRITE WR

Soft Wax/resin

RECOMMENDED APPLICATIONS



LOGISTICS




PACKAGING



CHEMICAL




FOOD & BEVERAGE



HORTICULTURE



AUTOMOTIVE



MEDICAL



ELECTRONICAL



HEALTH AND BEAUTY



TEXTILE

RECOMMENDED SUBSTRATES



CHEMICALS RESISTANCE



ALCOHOL



GASOLINE



GASOLINE + OIL



COMPLIANCES



ISEGA



T H E R M A L
T R A N S F E R
R I B B O N

E.U.R.O. Srl
Via Pacinotti, 28
30033 Noale (VE)

Tel. +39 041 3195211
ttr@eurosrl.com
www.eurosrl.com

All information in the datasheet has been produced for the exclusive use of E.u.r.o. s.r.l. Any reproduction, even partial, is prohibited. The BEE trademark is registered. The measured values may slightly vary in a different environment. The information contained may change without notice or notification. The information presented here is a general guideline, for further information please contact our offices. All product certifications have been registered with the original codes of the raw material.